

# Material Safety Data Sheet-COSHH

Catalyst (Methyl Ethyl Ketone Peroxide)

Catalyst/MSDS/Jan15

## 1. Identification of the substance/preparation and the company undertaking

### Chemical identity

Methyl ethyl ketone peroxide in dimethyl phthalate

### Supplier

Tuff Waterproofing Limited Unit 5 First Avenue Sherburn in Elmet LS25 6PD

### Emergency Telephone number

01977 680 250 Fax 01977 680 284

## 2. Composition/Information on ingredients

This product is to be considered as a preparation in conformance to EU directives.

### Chemical description

Methyl ethyl ketone peroxide in demethyl phthalate

Number	%W/W	Cas number	Chemical Name
1	-	330 1338-23-4	Methyl ethyl ketone peroxide
2	63.0	131-11-3	Dimethyl phthalate
3	1.0	78-93-3	Methyl ethyl ketone

Number	EINECS/ELINCS	EEC number	Symbol(s)	Risk phrase(s)
1	2156612	-	E C	R2, R20/22, R34, R7
2	2050116	-	none	none
3	2011590	606-002-003	F	R11

### Other information

Balance: non-hazardous ingredients.

## 3. Hazards Identification

May cause fire.

Harmful by inhalation and if swallowed.

Causes burns.

## 4. First aid measures

### Symptoms and effects

Harmful by inhalation and if swallowed. Causes burns. Risk of serious damage to eyes.

Affected Area	Action
General	Call a physician immediately.
Inhalation	Move to fresh air, rest, half-upright position, loosen clothing. Use Oxygen or artificial respiration if there is any difficulty in breathing. Seek medical advice after significant exposure.

# Material Safety Data Sheet

Catalyst (Methyl Ethyl Ketone Peroxide)

Catalyst/MSDS/Jan15

Skin	Remove all contaminated clothing immediately. Wash off with plenty of soap and water. Always seek medical advice. Launder clothes before re-use.
Eye	Rinse immediately and for as long as possible with plenty of water. Eyelids should be held away from the eyeball to ensure thorough rinsing. Always seek medical advice.
Ingestion	Only when conscious, rinse mouth, give plenty of water to drink (approx. 500ml). DO NOT induce vomiting. Seek medical advice.
Advice to physician	No additional information available.

## 5. Fire fighting measures

### Extinguishing media

Waterspray, foam, fire extinguishing powder, carbon dioxide. Extinguish a small fire with powder or carbon dioxide then apply water to prevent re-ignition.

### Unsuitable extinguishing media

Halones.

### Special exposure hazards

If involved in a fire, it will support combustion. In case of fire and/or explosion do not breathe fumes.

### Hazardous decomposition/combustion products

Not determined.

### Protective equipment

Wear suitable protective clothing. Wear self-contained breathing apparatus.

### Other information

Cool closed containers with water.

## 6. Accidental release measures

### Personal precautions

Avoid contact with skin and eyes. For personal protection see Section 8

### Environmental precautions

Collect as much as possible in a clean container for (preferable) re-use or disposal. Do not empty into drains.

### Methods for cleaning up

The waste should NOT be confined. Absorb the remainder with e.g. vermiculite.

### Other information

For personal protection see Section 8.

# Material Safety Data Sheet

Catalyst (Methyl Ethyl Ketone Peroxide)

Catalyst/MSDS/Jan15

## 7. Handling and storage

### Handling

Never weigh out in the storage room. Keep product and emptied container away from heat and storage of ignition. No sparking tools should be used. Avoid shock and friction. Confinement must be avoided. Do not pipet by mouth. Do not inhale. Never bring peroxide into direct contact with accelerator during processing. Weigh out and add peroxide and accelerator separately.

### Fire and explosion prevention

Use explosion protected equipment. Keep away from sources of ignition. No smoking.

### Storage requirements

Keep away from reducing agents, e.g. amines, acids, alkali, heavy metal compounds (e.g. accelerators, dryers, metal soaps). Store in accordance with local/national regulations. Store in a dry well ventilated place away from sources of heat and direct sunlight. Do not mix with peroxide accelerators. Do not mix with reducing agents. Keep container tightly closed in a cool well-ventilated place. Keep container upright to prevent leakage. Confinement must be avoided.

### Other information

When using do not eat, drink or smoke. Wash thoroughly after handling. Keep working clothing separately and do not take them home.

## 8. Exposure and controls/personal protection

### Engineering controls

Ensure good ventilation and local exhaustion of the working area. Explosion proof ventilation recommended.

### Exposure limits

Name	Exposure limits
Methyl ethyl ketone peroxide	OES-STEL (1993) 1.5mg/m <sup>3</sup>
Methyl ethyl ketone	OES-TWA (1993) 590.OMG/M <sup>3</sup>
	OES-STEL (1993) 885.OMG/M <sup>3</sup>

### Personal protection

Respiratory	Do not breathe vapour. Ensure good ventilation and Local exhaustion of the working area.
Hand	Wear suitable gloves or neoprene or synthetic rubber
Eye	Wear eye/face protective clothes and gloves. A face Shield is preferred over goggles.
Skin and body	Wear suitable protective clothing and gloves. Take off contaminated clothing immediately.
Other information	Launder clothes before re-use.

## 9. Physical and chemical properties

### Appearance

Liquid

### Colour

Clear an colourless

# Material Safety Data Sheet

Catalyst (Methyl Ethyl Ketone Peroxide)

Catalyst/MSDS/Jan15

## Odour

Faint

## Boiling point/range

Do not distil (decomposes)

## Melting point/range

Turbid <-10°C

## Flash point

52°C (Setaflash ISO 3679)

## Flammability

Not determined

## Auto ignition

218°C (DIN 51794)

## Explosive properties

No

## Explosion limits

Not applicable

## Oxidising properties

Not applicable

## Vapour pressure

Not determined

## Density

1180kg/m<sup>3</sup> (20°C)

## Bulk density

Not applicable

## Solubility in water

Partly mixable with water

## Solubility in other solvents

Phthalates

## pH value

Slightly acidic character

## Partition coefficient n-octanol/water

Not determined

## Relative vapour density air = 1

Not determined

## Viscosity

20 MM<sup>2</sup>/SEC. (20°C)

## Active oxygen content

8.8-9.0%

# Material Safety Data Sheet

Catalyst (Methyl Ethyl Ketone Peroxide)

Catalyst/MSDS/Jan15

## Peroxide content

33%

## SADT

60°C. See also section 10: Other information

## Specific conductivity

Not determined

## 10. Stability and reactivity

### Stability

A dangerous, self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be caused by direct contact with incompatible substances or by thermal decomposition at or above the following temperature: +60°C.

### Conditions to avoid

Violent reactions may be expected with acid, alkali, heavy metals and reducing agents. Avoid contact with rust. Confinement must be avoided. Do not mix with peroxide accelerators. Do not mix with reducing agents.

### Materials to avoid

Use only Stainless Steel 31.6. PVC, polythene or glass-lined equipment.

### Hazardous decomposition products

Not determined.

### Other information

The SADT (Self Accelerating Decomposition Temperature) is an experimentally derived temperature at which the product in a typical package will undergo self-accelerating decomposition.

## 11. Toxicological information

### Acute toxicity (Base on Methyl ethyl ketone peroxide 33%)

Oral LD50 rat: 1017mg/kg (**Methyl ethyl ketone peroxide 40%**)

Dermal LD50 rat: 4000mg/kg (**Methyl ethyl ketone peroxide 40%**)

Inhalation LC50 rat: 17mg/1; 4 hours exposure time (**Methyl ethyl ketone peroxide 40%**)

### Skin (irritation)

Corrosive (33%)

### Eye (irritation)

Severely irritating/corrosive (Methyl ethyl ketone peroxide 33%)

### Genotoxicity (irritation)

Ames test: Not mutagenic

### Acute toxicity (based on: Dimethyl phthalate)

Oral LD50 rat: >2400mg/kg

Dermal LD50 rabbit: 10.000mg/m<sup>3</sup>

Inhalation LC50 rat: 9.3mg/m<sup>3</sup> (6.5 hours)

# Material Safety Data Sheet

Catalyst (Methyl Ethyl Ketone Peroxide)

Catalyst/MSDS/Jan15

## Skin (irritation)

Moderately irritating

## Eye (irritation)

Minimal irritation

## Acute toxicity (based on: Methyl ethyl ketone)

Oral LD50 rat: 2737mg/kg

Dermal LD50 rabbit: 6480mg/kg

Inhalation LC50 rat: 23.5000mg/m<sup>3</sup>

## Skin (irritation)

Moderately irritating

## Eye (irritation)

Moderately irritating

## 12. Ecological information

### Ecotoxicity (based on: Methyl ethyl ketone peroxide 33%)

Fish Acute toxicity, 96h-LC50 = 44.2mg/l (Poecilia reticulata)

Bacteria Activated sludge respiration inhibition test EC50 = 48.0mg/l

### Fate

Degradation Biotic Readily biodegradable (closed bottle test)

### Ecotoxicity (based on: Dimethyl phthalate)

Fish Lepomis macrochirus: 96h-LC50: 3.22g/l

Algae Selenastrum capricornutum: 39.8mg/l (96h-LC50)

### Fate

Degradation Biotic Readily biodegradable (closed bottle test)

### Other information

Naturally occurring substance

## 13. Disposal Considerations

### Product

Probably in controlled incineration but according to local regulations. The waste should NOT be confined. Absorb the remainder with e.g. vermiculite.

### Contaminated Packaging

Collect for recycling or most probably controlled incineration.

### Other information

Dilute before burning with organic solvents. Controlled incineration according to local regulations (e.g. burn in small portions on a remote place, using a torch with a long rod to ignite the material).

# Material Safety Data Sheet

Catalyst (Methyl Ethyl Ketone Peroxide)

Catalyst/MSDS/Jan15

## 14. Transport information

<b>Land Transport</b>	
<b>ADR Class</b>	<b>ADR Item Number</b>
5.2	5b
<b>RID Class</b>	<b>RID Item Number</b>
5.2	5b
<b>Hazard Identification Number</b>	<b>Substance Identification Number</b>
Trem Card: cefic tec(r) -52g01	UN Number: 3105
<b>Proper Shipping Name</b>	
Organic peroxide type d, liquid: (Methyl ethyl ketone peroxide)	

## 15. Regulatory information

<b>Chemical Identity</b>	
Methyl ethyl ketone peroxide, in dimethyl phthalate	
<b>Labelling according to EC directives</b>	
EEC number: Not applicable	
<b>Classification based on:</b>	
<b>Symbol(s)</b>	
OXIDIZING	CORROSIVE
<b>Risk phrase(s)</b>	
R7	May cause fire
R20/22	Harmful by inhalation and if swallowed.
R34	Causes burns
<b>Safety phrase(s)</b>	
S3/7	Keep container closed in a well-ventilated place.
S14	Keep away from reducing agents e.g. amines, acids, Alkalis, heavy metal compounds. (e.g. accelerators, dryers, metal soaps).
S26	In case of contact with eyes, rinse immediately with Plenty of water and seek medical advice.
S36/37/39	Wear suitable protective clothing, gloves and eye/ face protection.
S50	Do not mix with peroxide accelerators. Do not mix with reducing agents.
<b>Other information</b>	
Wassergefährdungsklasse (WGK) (Germany)	1 (own classification)